

Turbo Drive® Screw Anchor

2-1/4" Socket Turbo Drive® Screw Anchor (Patent Pending)



- One piece cast steel hub for increased torque and bending strength
- Four flute hub to break up tough soils
- 10,000 ft-lb torque rating
- Light duty with 3/8" helix thickness
- Heavy Duty with 1/2" helix thickness
- Use with standard 10,000 ft-lb installing tool (5-1/4" bolt circle tool) or 15,000 ft-lb installing tool (7-5/8" bolt circle)



Turbo Drive® Screw Anchor

Standard 2-1/4" Socket Drive – 10,000 Ft. Lb. Ultimate Installing Torque; with 3/8" helix thickness; for Standard Installing Tool			
Turbo Drive® Catalog Number	Helix Size (Inches)	Tapped for Rod Size (inches)	Standard Pack / Pallet Qty
TD225-82	8	5/8	4/120
TD225-84	8	3/4 or 1	4/120
TD225-102	10	5/8	4/120
TD225-104	10	3/4 or 1	4/120
TD225-114	12	3/4 or 1	4/48
TD225-134	14	3/4 or 1	3/36

Note: Use the **Standard** socket drive with 3/8" helix thickness when dense but generally uniform soil is present and helix strength is sufficient.

Heavy Duty 2-1/4" Socket Drive – 10,000 Ft. Lb. Ultimate Installing Torque; with 1/2" helix thickness; for Standard Installing Tool			
Turbo Drive® Catalog Number	Helix Size (Inches)	Tapped for Rod Size (inches)	Standard Pack / Pallet Qty
TDH225-84	8	3/4 or 1	4/120
TDH225-104	10	3/4 or 1	4/120
TDH225-114	12	3/4 or 1	4/48
TDH225-134	14	3/4 or 1	3/36

Note: Use the **Heavy Duty** socket drive with 1/2" helix when rocks, gravel, glacial till are present and additional helix strength is required to penetrate the tough soils.

